



ENGINEERED OAK FLOORING – INSTRUCTIONS FOR USE

DRYMAR oak flooring is very durable and resistant to water and dirt. We recommend proper maintenance of the floor, which will significantly extend its service life.

1. IMPORTANT

To ensure proper curing of the Hardwax oil after the installation of the floor, we recommend not washing the floor or applying maintenance oil for 30 days. Water or other wet stains should be removed immediately using a lint-free cloth. Immediately after installation the floor can be vacuumed or swept.

2. LONG-LASTING SHINE – TIPS AND RECOMMENDATIONS

- Dust and sand may cause scratches on the floor surface; therefore, a good quality doormat should be placed in front of entrance doors.
- Chair legs and other furniture legs should be protected with dedicated felt pads.
- Bowls and pet feeding dishes should be placed on protective mats.
- Heavy furniture should be lifted rather than dragged.
- Regular vacuuming or sweeping reduces the risk of scratching the floor.
- When cleaning floors, excessive and frequent use of water should be avoided, as it may damage the wood.
- Stains should be removed immediately with a damp cloth.
- The room temperature should be maintained between 18–22°C, while humidity should remain between 40–60%.
- Underfloor heating should be maintained according to recommendations for wooden floors.

3. CLEANING AND MAINTENANCE INFORMATION

FREQUENCY	CLEANING / MAINTENANCE METHOD
After installation	Vacuuming or sweeping
Daily / weekly	Vacuuming or sweeping
Weekly / monthly	Cleaning with parquet floor cleaner
Once per year (normal use)	Maintenance with floor care oil
2 – 3 times per year (intensive use)	Maintenance with floor care oil
Stains or damage	Contact point of purchase

4. CLEANING

We recommend cleaning the floor once a week / once a month (depending on the intensity of use) with a cleaner designed for oiled wooden floors. Avoid using strong cleaning agents.

- Before using cleaning products, read the instructions carefully.
- Remove dust and dirt by vacuuming or sweeping the floor.
- Add approximately 100 ml floor cleaner to 5 liters of water.
- Clean the floor using a well-wrung mop.
- After cleaning, wait until the floor dries completely. Only walk on the floor once the wood is fully dry.

5. MAINTENANCE

We recommend maintaining the floor 1–2 times per year using floor maintenance oil. In areas of intensive use, such as kitchens or high-traffic spaces, more frequent maintenance is recommended (3–4 times per year).

6. STAINS OR DAMAGE

To reduce the risk of permanent stains or damage, stains should be removed immediately using damp cloth or other appropriate method.

Useful tips:

- Black marks / shoe rubber – remove with an eraser.
- Other stains – mix green soap or vinegar with water and remove the stain with a damp cloth or brush. Then, if necessary, apply maintenance oil.
- **Avoid using strong alcohol-based cleaning products!**

If none of these methods are effective, we recommend contacting the supplier or a flooring specialist.